

## Receiver Specification

Our Part No		13M03TH-25YE32-4H12	
Size	Diameter 13mm	Total Height	2.7 mm
No.	Item	Specification	Testing Condition
1.	Rated Imp	32ohm $\pm$ 15%	At 1 kHz 1.0V
2.	D.C Impedance	29.7ohm $\pm$ 10%	At 20°C
3.	Output S.P.L.	108 $\pm$ 3dB	At 1mW IEC318 at 1KHz
4.	Input Power	Rated Power: 20mW	Max Power: 30mW
5.	Frequency Range	200---5KHz	Output S.P.L. -10dB
6.	Operation	Must Be Normal	Program Source 20mW
7.	Buzzes & Rattles	Must Be Normal	Sin Wave 0.8V
8.	Load Testing	After Test Meet 1&6	20mW 48hours White Noise
9.	Distortion	5% Max	Input Rated Power at 1000Hz
10.	Heat Testing	After Test 7&8&9	55°C $\pm$ 2°C 16hours
11.	Cold Testing	After Test 7&8&9	-20°C $\pm$ 3°C 16hours
12.	Humidity Testing	After Test 7&8&9	40°C $\pm$ 2°C 90~95% R.H. 48hours
13.	Insulation Resistance	1M $\Omega$	Dc100v FRA. And TER.
14.	Magnet Size	$\varnothing$ 6.5 $\times$ 0.8	N38
15.	Net Weight	1.2g/PC	
16.	Polarity	When a positive D.C voltage is applied to the terminal marked (+) or red, the diaphragm should move to the front.	

