

Receiver Specification

Our Part No		15M14TH-25WE32-6J28	
Size	Diameter 15mm	Total Height	2.8mm
No.	Item	Specification	Testing Condition
1.	Rated Imp	32ohm \pm 15%	At 1 kHz 1.0V
2.	D.C Impedance	29.7hm \pm 10%	At 20°C
3.	Output S.P.L.	101 \pm 3dB	At 1mW IEC318 1KHz
4.	Input Power	Rated Power: 10mW	Max Power: 20mW
5.	Frequency Range	200----4KHz	Output S.P.L. -10dB
6.	Operation	Must Be Normal	Program Source 10mW
7.	Buzzes & Rattles	Must Be Normal	Sin Wave 0.56V
8.	Load Testing	After Test Meet 2&7	10mW 96hours White Noise
9.	Distortion	5% Max	Input Rated Power at 1000Hz
10.	Heat Testing	After Test 7&8&9	+60°C \pm 3°C 48hours
11.	Cold Testing	After Test 7&8&9	-25°C \pm 3°C 48hours
12.	Humidity Testing	After Test 7&8&9	40°C \pm 2°C 90~95% R.H. 48hours
13.	Insulation Resistance	1M Ω	Dc100v FRA. And TER.
14.	Magnet Size	\varnothing 6.5 \times 0.8	N38
15.	Net Weight	1.4 g/PC	
16.	Polarity	When a positive D.C voltage is applied to the terminal marked red, the diaphragm should move to the front.	

