

## Receiver Specification

Our Part No		32P02-60WE150-6F21	
Size	Diameter 32mm	Total Height	15.2mm
No.	Item	Specification	Testing Condition
1.	Rated Imp	150ohm $\pm$ 15%	At 0.1Vrms 1KHz
2.	Resonance Freq	---Hz $\pm$ 20%	Without Baffle
3.	Output S.P.L.	103 $\pm$ 3dB	At 100mV IEC318 1KHz
4.	Input Power	Rated Power: 10mW	Max Power: 20mW
5.	Frequency Range	300---4KHz	Output S.P.L. -10dB
6.	Operation	Must Be Normal	Program Source 10mW
7.	Buzzes & Rattles	Must Be Normal	Sin Wave 0.6V
8.	Load Testing	After Test Meet 2&7	10mW 96hours White Noise
9.	Distortion	5% Max	Input Rated Power at 1000Hz
10.	Heat Testing	After Test 7&8&9	+60°C $\pm$ 3°C 48hours
11.	Cold Testing	After Test 7&8&9	-25°C $\pm$ 3°C 48hours
12.	Humidity Testing	After Test 7&8&9	40°C $\pm$ 2°C 90~95% R.H. 48hours
13.	Insulation Resistance	1M $\Omega$	Dc100v FRA. And TER.
14.	Magnet Size	$\varnothing$ 22 $\times$ $\varnothing$ 10 $\times$ 3.7	Y30
15.	Net Weight	15.5 g/PC	
16.	Polarity	/	

