

Mylar Speaker Specification

Our Part No		40P05-70WE8-4A15	
Size	Diameter 40mm	Total Height	4.6 mm
No.	Item	Specification	Testing Condition
1.	Rated Imp	8ohm \pm 15%	At 1 kHz 1.0V
2.	Resonance Freq	420Hz \pm 20%	Without Baffle
3.	Output S.P.L.	81 \pm 3dB	At 1m 1W 600, 800, 1K, 1.2KHz Average
4.	Input Power	Rated Power: 0.25W	Max Power: 0.5W
5.	Frequency Range	F0---3KHz	Output S.P.L. -10dB
6.	Operation	Must Be Normal	Program Source: 0.25W
7.	Buzzes & Rattles	Must Be Normal	Sin Wave 1.41V
8.	Load Test	After Test Meet 2&7	0.25W 96hours White Noise
9.	Distortion	5% Max	0.25W 1000Hz
10.	Heat Test	After Test 7&8&9	+60°C \pm 3°C 48hours
11.	Cold Test	After Test 7&8&9	-20°C \pm 3°C 48hours
12.	Humidity	After Test 7&8&9	40°C \pm 2°C 90~95% R.H. 48hours
13.	Insulation Resistance	1M Ω	Dc100v FRA. And TER.
14.	Magnet	Φ 9.5 \times 1.5	N35
15.	Net Weight	5.5g/PC	
16.	Polarity		

